

# RIOT



## FORDONSSPECIFIKATIONER

### MOTOR

	RIOT 858 SNO PRO	RIOT 600 SNO PRO	RIOT 858 MED ATAC OCH EPS
Engine Type	858, 2-Stroke	600, 2-Stroke	
Displacement <span>?</span>	858cc	599cc	
Cooling <span>?</span>	Liquid	Liquid	
Cylinders <span>?</span>	2	2	
Bore x Stroke <span>?</span>	85 x 75.6 mm	73.8 x 70 mm	
Lubrication <span>?</span>	Electronic Injection	Electronic Injection	
Ignition	Digitally Controlled CDI	Digitally Controlled CDI	
Engine Stator Output <span>?</span>	270W @ 3000 RPM	270W @ 3000 RPM	
Fuel Delivery <span>?</span>	Next Generation C-TEC2	Dual Stage Injection	
Exhaust	APV II with Full Stainless Steel Exhaust & EGT Sensors	APV with Tuned Pipe, Pipe Sensor and Stainless Steel Manifold and Muffler	
Fuel Capacity	39.4 L	39.4 L	
Oil System Capacity	2.8 L	2.8 L	
Coolant System Capacity	5.1 L	5.1 L	
Minimum Octane <span>?</span>	91	91	

**DRIVLINA**

	<b>RIOT 858 SNO PRO</b>	<b>RIOT 600 SNO PRO</b>	<b>RIOT 858 MED ATAC OCH EPS</b>
Drive Clutch <span>?</span>	ADAPT	ADAPT	
Driven Clutch <span>?</span>	ADAPT	ADAPT	
Drive System	AC Trail Belt Drive	AC Trail Belt Drive	
Brakes	Stealth Hydraulic Master Cylinder	Stealth Hydraulic Master Cylinder	
Clutch Calibration <span>?</span>	0-1,524 m	0-1,524 m	
Gearing	27/60	27/60	
Chain Pitch	Belt	Belt	
Track Drive Sprocket <span>?</span>	9 Tooth, 7.2 cm Pitch, Exvolute	9 Tooth, 7.2 cm Pitch, Exvolute	
Reverse	Push-Button Engine	Push-Button Engine	

**FJÄDRING**

	<b>RIOT 858 SNO PRO</b>	<b>RIOT 600 SNO PRO</b>	<b>RIOT 858 MED ATAC OCH EPS</b>
Front Suspension	AWS 39	AWS 39	
Ski Shocks	AC5S	AC5S	
Sway Bar <span>?</span>	Standard	Standard	
Front Travel	19.1 cm	19.1 cm	
Rear Suspension	CROSS-ACTION w/ 3-Wheel Rear Axle Assembly, Torque-Sensing Link Rear Arm, and Adjustable Torsion Springs	CROSS-ACTION w/ 3-Wheel Rear Axle Assembly, Torque-Sensing Link Rear Arm, and Adjustable Torsion Springs	

	RIOT 858 SNO PRO	RIOT 600 SNO PRO	RIOT 858 MED ATAC OCH EPS
Front Track Shock	AC5S	AC5S	
Rear Track Shock	AC5S	AC5S	
Rear Travel	34.3 cm	34.3 cm	

## DIMENSIONER

	RIOT 858 SNO PRO	RIOT 600 SNO PRO	RIOT 858 MED ATAC OCH EPS
Overall Chassis Length	331.5 cm	331.5 cm	
Overall Chassis Width	122-124.5 cm	122-124.5 cm	
Overall Chassis Height	124.5 cm	124.5 cm	
Track Type	Hurricane	Hurricane	
Track Width	38 cm	38 cm	
Track Length	371 cm	371 cm	
Lug	44.5 mm	44.5 mm	
Pitch 	7.2 cm	7.2 cm	
Ski Stance	96.5-101.6 cm Adjustable	96.5-101.6 cm Adjustable	
Ski Type/Width	G2 ProClimb - 18 cm	G2 ProClimb - 18 cm	
Runner Type	Single Runner w/ Carbide	Single Runner w/ Carbide	

## INSTRUMENTERING

	<b>RIOT 858 SNO PRO</b>	<b>RIOT 600 SNO PRO</b>	<b>RIOT 858 MED ATAC OCH EPS</b>
Type of Gauge	Sport	Sport	
Speedometer	Digital	Digital	
Tachometer <span>?</span>	Digital	Digital	
Odometer	Digital	Digital	
Fuel	Digital	Digital	
Oil	LCD Icon	LCD Icon	
Coolant	Digital Bar Graph	Digital Bar Graph	
Clock	N/A	N/A	
Battery Voltage	N/A	N/A	
Altimeter	N/A	N/A	
Hours	Digital	Digital	

## FUNKTIONER

	<b>RIOT 858 SNO PRO</b>	<b>RIOT 600 SNO PRO</b>	<b>RIOT 858 MED ATAC OCH EPS</b>
Color	Medium Green/Black	Medium Green/Black	
Heat Exchanger <span>?</span>	Front/ Long Tunnel	Front/ Long Tunnel	
Starter	Push-Button Engine Start	Push-Button Engine Start	
Handlebars	Hooked	Hooked	
Lighting	LED	LED	
Seating	Trail	Trail	

	<b>RIOT 858 SNO PRO</b>	<b>RIOT 600 SNO PRO</b>	<b>RIOT 858 MED ATAC OCH EPS</b>
<b>Standard Accessories</b>	12V Outlet, Sport Front Bumper, Integrated Goggle Holder, Hand & Thumb Warmers, Ice Scratchers, Standard Brake Disc, Ratio Steering, ATACH Rear Storage, Tether Switch, Visor Plug-In	12V Outlet, Sport Front Bumper, Integrated Goggle Holder, Hand & Thumb Warmers, Ice Scratchers, Standard Brake Disc, Ratio Steering, ATACH Rear Storage, Tether Switch, Visor Plug-In	
<b>Windshield</b>	14 cm Low-Height	14 cm Low-Height	

*Fordonsspecifikationer kan ändras.*